

金屬磨料總匯

METAL ABRASIVES

福建泉州市金星鋼丸有限公司
JINXING STEEL SHOT CO., LTD. CHINA

環保 節能 低碳 高效

Environmental protection, Energy saving, High efficiency

型號 Size	S70	S110	S170	S230	S280	S330	S390	S460	S550	S660
低碳鋼丸 Low carbon steel shot										
型號 Size	S110	S170	S230	S280	S330	S390	S460	S550	S660	S780
高碳鋼丸 High carbon steel shot										
型號 Size	G120	G80	G50	G40	G25	G18	G16	型號 (Size)	G18	G25
高碳鋼砂 High carbon steel grit								石榴鋼砂 Branite cutting grit		
規格 Size	0.6mm	0.8mm	1.0mm	0.3mm	0.5mm	規格 Size	0.6mm	0.8mm	1.0mm	
不銹鋼丸 Stainless steel shot						鋅丸 Zinc shot				
規格 Size	0.6mm	0.8mm	1.0mm	0.3mm	0.5mm	規格 (Size)	0.8mm	1.0mm	規格 (Size)	1.0mm
強化鋼丸 Steel cut wire shot (conditioned)						鋁丸 Aluminum shot			銅丸 Copper shot	

規格型號不局限于以上樣品，可按客戶需求供貨。
other sizes available upon request

Steel Shot			
Chemical composition	C:0.80-1.2%; Si:≥0.4%; Mn:0.60-1.2%; S:≤0.05%; P:≤0.05%		
Density	>7.3g/cm ³		
Hardness(± 3HRC)	HRC40-50	HRC50-60	HRC60-65
Microstructure	It should be uniformly tempered martensite with fine, well distributed carbides. Network carbides. Decarbonized surfaces. Inclusions or quench cracks are undesirable.		
We accept Special orders and can satisfy special requirements from customers.			

Number of screen	Standard (mm)	Screw mesh (inch)	S930	S780	S660	S550	S460	S390	S330	S280	S230	S170	S110	S70
			SS280	SS240	SS200	SS170	SS140	SS120	SS100	SS80	SS70	SS60	SS40	SS30
6	3.35	0.132	0											
7	2.8	0.111	-	0										
8	2.36	0.0937	≥85	-	0									
10	2.00	0.0787	≥97	≥85	-	0	0							
12	1.70	0.0661		≥97	≥85	-	≤5	0						
14	1.40	0.0555			≥97	≥85	-	≤5	0					
16	1.18	0.0469				≥97	≥85	-	≤5	0				
18	1.00	0.0394					≥97	≥85	-	≤5	0			
20	0.850	0.0331						≥96	≥85	-	≤10	0		
25	0.710	0.0278							≥96	≥85	-	≤10		
30	0.600	0.0234								≥96	≥75	-	0	
35	0.500	0.0197									≥97	-	≤10	
40	0.425	0.0165										≥85	-	0
45	0.355	0.0139										≥97	-	≤10
50	0.300	0.0117											≥80	-
80	0.180	0.007											≥90	≥70
120	0.125	0.0047												≥90

SS-JIS S-SAE O-ALL pass The Figure in the square indicates the percentage allowed to remain on the screen.

<http://www.jxabrasives.com/>

sales@jxabrasives.com