

**金屬磨料總匯**  
**METAL ABRASIVES**

福建泉州市金星鋼丸有限公司  
JINXING STEEL SHOT CO., LTD. CHINA

環保 節能 低碳 高效  
Environmental protection, Energy saving, High efficiency

型號 Size	S70	S110	S170	S230	S280	S330	S390	S460	S550	S660
低碳鋼丸 Low carbon steel shot										
型號 Size	S110	S170	S230	S280	S330	S390	S460	S550	S660	S780
高碳鋼丸 High carbon steel shot										
型號 Size	G120	G80	G50	G40	G25	G18	G16	型號 (Size)	G18	G25
高碳鋼砂 High carbon steel grit								石榴鋼砂 Granite cutting grit		
規格 Size	0.6mm	0.8mm	1.0mm	0.3mm	0.5mm	規格 Size	0.6mm	0.8mm	1.0mm	
不銹鋼丸 Stainless steel shot						鋅丸 Zinc shot				
規格 Size	0.6mm	0.8mm	1.0mm	0.3mm	0.5mm	規格 Size	0.8mm	1.0mm	規格 Size	1.0mm
強化鋼丸 Steel cut wire shot (conditioned)						鋁丸 Aluminum shot			銅丸 Copper shot	

規格型號不局限于以上樣品，可按客户需求供货。  
other sizes available upon request

Cut-wire Size (Inches)	Cut-wire Shot Size (mm)	Cast steel Shot Size
0.012	0.30	S-70
0.017 / 0.018	0.40 / 0.45	S-110
0.020 / 0.023	0.50 / 0.60	S-170
0.028	0.70	S-230
0.032 / 0.035	0.80 / 0.90	S-280
0.035 / 0.041	0.90 / 1.00	S-330
0.041 / 0.047	1.00 / 1.20	S-390
0.054	1.40	S-460
0.062	1.60	S-550
0.080	2.00	S-660
0.090	2.30	S-780
0.126	3.20	S-1110

Material	SIZES	WIRE	ROCKWELL HARDNESS RANGE	VICKERS HARDNESS RANGE
Steel	.012 inch - .062 inch (0.30mm - 1.60mm)	Carbon Spring Wire 1070 Class	45 - 52 C	446 - 595
		I High carbon 1070 Class	55 - 62 C	595 - 697
Stainless Steel	.014 inch - .125 inch (0.35mm - 3.2 mm)	Type 302/304 Spring Wire	45- 58 C	446 - 653
		Class I 316 & 430	30 - 35 C	302 - 345
Aluminum	.030 inch - .125 inch (0.76 mm - 3.2 mm)	Types 1100-1345	30-40 B	N/A
		Type 4043	40 B	
		Type 5356	70 B	
Copper	.020 inch - .125 inch (0.5 mm to 3.2 mm)	Alloy 102 or 110	50-65 B	N/A
Zinc	.030 inch - .125 inch (.76 mm - 3.2 mm)	Special High Grade Pure Zinc (99.995%)	20 - 30 B	N/A

<http://www.jxabrasives.co/>

[sales@jxabrasives.com](mailto:sales@jxabrasives.com)