

## 金屬磨料總匯

### METAL ABRASIVES

福建泉州市金星鋼丸有限公司  
JINXING STEEL SHOT CO., LTD. CHINA

環保 節能 低碳 高效  
Environmental protection, Energy saving, High efficiency

型號 Size	S70	S110	S170	S230	S280	S330	S390	S460	S550	S660
低碳鋼丸 Low carbon steel shot										
型號 Size	S110	S170	S230	S280	S330	S390	S460	S550	S660	S780
高碳鋼丸 High carbon steel shot										
型號 Size	G120	G80	G50	G40	G25	G18	G16	型號 (Size)	G18	G25
高碳鋼砂 High carbon steel grit								石輪鋼砂 Grain cutting grit		
規格 Size	0.6mm	0.8mm	1.0mm	0.3mm	0.5mm	規格 Size	0.6mm	0.8mm	1.0mm	
不銹鋼丸 Stainless steel shot						鋅丸 Zinc shot				
規格 Size	0.6mm	0.8mm	1.0mm	0.3mm	0.5mm	規格 Size	0.8mm	1.0mm	規格 (Size)	1.0mm
強化鋼丸 Steel cut wire shot (conditioned)						鋁丸 Aluminum shot			銅丸 Copper shot	

規格型號不局限于以上樣品，可按客戶需求供貨。  
other sizes available upon request

Steel Grit				
Chemical composition	C:0.80-1.2%; Si≥0.4%; Mn:0.60-1.2%; S:≤0.05%; P:≤0.05%			
Density	>7.3g/cm <sup>3</sup>			
Hardness(± 3HRC)	HRC40-51	HRC47-56	HRC54-61	HRC61-65
We accept Special orders and can satisfy special requirements from customers.				

Number of screen	Standard (mm)	Screw mesh (inch)	G10	G12	G14	G16	G18	G25	G40	G50	G80	G120
			SG240	SG200	SG170	SG140	SG120	SG100	SG70	SG50	SG30	SG20
7	2.8	0.111	0									
8	2.36	0.0937	-	0								
10	2.00	0.0789	80	-	0							
12	1.70	0.0661	90	80	-	0						
14	1.40	0.0555		90	80	-	0					
16	1.18	0.0469			90	75	-	0				
18	1.00	0.0394				85	75	-	0			
20	0.85	0.0331					-	-	-			
25	0.71	0.0278					85	70	-	0		
30	0.60	0.0234						-	-	-		
35	0.50	0.0197						-	-	-		
40	0.425	0.0165						80	70	-	0	
45	0.355	0.0139							-	-	-	
50	0.300	0.0117							80	65	-	0
80	0.180	0.007								75	65	-
120	0.125	0.0049									75	60
200	0.075	0.0029										70

SG-JIS G-SAE O-ALL pass The Figure in the square indicates the percentage allowed to remain on the screen.

<http://www.jxabrasives.com/>

[sales@jxabrasives.com](mailto:sales@jxabrasives.com)